

Series | Bellows vacuum cups SB

Bellows vacuum cups, 1.5 and 4.5 bellows, with fully assembled fitting – SP-B

Bellows vacuum cups, 1.5 and 4.5 bellows, with fully assembled fitting – SP-B



Product notes	Advantage
	 > High suction force > Fast cycle times possible > Very resistant to wear (Tepuflex®) > Compatible with established products from other vendors

Technical data							Accessories			
Item no.	Model	Connection thread	Ī	Number of folds	Material / Color	Filter disc:	Spare vacuum cup:	Stiffening ring:		
	Complete v	acuum cups, 1.5 fo	olds with	fitting & f	ilter screen					
22.020.020*	SP-B1-20	G1/8-male, M5-female	9	1.5	Tepuflex® (or), SI (tr), CR (sw)	78.200	23.020.026*			
22.030.033*	SP-B1-30	G1/8-male, M5-female	9	1.5	Tepuflex® (or), SI (tr), CR (sw)	78.201	23.030.037*			
22.040.045*	SP-B1-40	G1/8-female	9	1.5	Tepuflex® (or), SI (tr), CR (sw)	78.202	23.040.045*			
22.050.056*	SP-B1-50	G1/8-female	12	1.5	Tepuflex® (or), SI (tr), CR (sw)	78.203	23.050.054*			
	Complete v	acuum cups, 4.5 fo	olds with	fitting & f	ilter screen					
24.030.039*	SP-B4-30	G1/8-female	21	4.5	CR (sw)		25.030.026.9	78.001		
24.040.074*	SP-B4-40	G1/8-female	20	4.5	SI (tr), CR (sw)		25.040.027*	78.002		
24.050.087*	SP-B4-50	G1/8-female	30	4.5	SI (tr), CR (sw)		25.050.028*	78.003		

Bellows vacuum cups with fully assembled fitting

Example:



or



- High process reliability thanks to permanently installed fitting
 Worn sealing lips can be replaced if necessary







Series | Bellows vacuum cups SB



Bellows vacuum cups, 1.5 and 4.5 bellows, with fully assembled fitting – SP-B

Dimensions





1 = Filter screen 2 = Aluminum

Item no.	Drawing	Ø D [mm]	Ø d2 [mm]	Ø d4 [mm]	Ø d5 [mm]	G1	G2	H [mm]	h1 [mm]	h3 [mm]	sw
Complete vacuun		, , ,				1	1		, į		1
22.020.020*	А	21		11	24	M5	G1/8	27	6.5		17
22.030.033*	А	33		18.5	37	M5	G1/8	35	6.5		17
22.040.045*	А	43		23	46	G1/8		35			12
22.050.056*	А	53		32	58	G1/8		42			12
Complete vacuun	n cups, 4.5 fold	ds with fittir	ng & filter so	creen			•	·			
24.030.039*	С	31		22		G1/8		40			12
24.040.074*	С	41		29		G1/8		51			12
24.050.087*	С	51		37		G1/8		61			12



